

Product Code | Code Produit | Código Producto

B 50 NA | D 50 NA

STYLE 50

Type		Style	Form	Suffix/Connection				Terminal blocks			Suffix/Customer	
				Suffix	Switch	Voltage	Current	AWG	Torque	Wire type		
B	Button	50	Q Square	VIII NA IX NA VIII NA bicolor IX NA bicolor	SPST-NO	30 V DC	0.5 A	28 - 18	1,5 Lb. In.	Cu	16	DMD 16x16
D	Display			SPDT	30 V DC 50 V AC	0.5 A 1 A	TH				Thyssen	
W	W-Indicator			R Round	OTIS	OTIS						

B 50 Q IX NA
21 - 05 - 00 - 10 12 - 30 V

Housing		Touchplate/Plate		Protection		LED Color		LED Voltage/LED Current	
01		00	without	00	Protection IP 40 (IEC 60529) Type 1 (UL50) Class 0	unicolor		VIII, IX	
03	Plastic, black	01	Stainless steel, non-directional V2A, matt	01	Protection against water and vandalism IP 54 (IEC 60529) Type 1 (UL50) Class 1	10	red	0 V	without LED
04	Cr-p (Chrome, polished)	02	Stainless steel, TiN (brass color), non-directional V2A, TiN, matt	02	Protection ⁽²⁾ against water and vandalism IP 54 (IEC 60529) Type 1 (UL50) Class 2	20	blue	6 V AC/DC	40 mA
05	Cr-m (Chrome, matted)	03	#8 Stainless steel, black color, mirrored V2A, black	03	Protection ⁽²⁾ against water and vandalism IP 54 (IEC 60529) Type 1 (UL50) Class 3+	30	green	12-30 V AC/DC	40 mA
06	TiN, polished	04	#8 Stainless steel, mirrored V2A, poliirt			40	white	30-48 V AC/DC	40 mA
07	TiN, matted	05	#8 Stainless steel, TiN (brass color), mirrored V2A, TiN, poliirt			50	yellow	VIII bicolor, IX bicolor	
08	Cr-p-black (Chrome, black polished)	20	Plastic, clear ⁽¹⁾			bicolor		12 - 30 V DC	45 mA
09	Cr-m-black (Chrome, black matted)	21	Plastic, red ⁽¹⁾			13	red/green	30 - 48 V DC	45 mA
XX	Chrome, color					31	green/red		
						23	blue/green		
						25	blue/yellow		
						42	white/blue		

⁽¹⁾ only D50

⁽²⁾ only with Housing 04...09



E469509
Elevator Accessory

Surrounding air temperature:
max. +55°C/ +131°F

