


Type	Style	Form	Suffix/Connection							
			Suffix	Switch	Voltage	Current	Terminal blocks			
								AWG	Torque	Wire type
EB	42	n/a	XI NA	SPST-NO SPDT	6 - 30 V DC 120 V DC 120 V AC	2 A 0.05 A 0.7 A	28 - 14	2.2 Lb. In.	Cu	
ED										Elliptical Display



Housing		Touchplate/Plate		Protection		LED Color		LED Voltage/LED Current	
37	#8 Stainless steel, mirrored V2A-p	01	Stainless steel, non-directional V2A, matt	00	Protection IP 40 (IEC 60529) Type 1 (UL50) Class 0	70	RGB	XI NA	
38	#8 Stainless steel, TiN (brass color), mirrored V2A, TiN-p	02	Stainless steel, TiN (brass color), non-directional V2A, TiN, matt					6 V DC	30 mA
39	#8 Stainless steel, black color, mirrored V2A, black-p	03	#8 Stainless steel, black color, mirrored V2A, black			12 - 120 V DC	0.2 W - 0.4 W		
		04	#8 Stainless steel, mirrored V2A, poliirt			30 - 120 V AC			
		05	#8 Stainless steel, TiN (brass color), mirrored V2A, TiN, poliirt						
		20	Plastic, clear ⁽¹⁾						
		21	Plastic, red ⁽¹⁾						

(1) only ED42



Surrounding air temperature:
max. +55 °C / +131 °F



E469509
Elevator Accessory