


Product Code | Code Produit | Código Producto

STYLE
42

MT 42 IX NA | MA 42 IX NA | MT 42 IX bicolor | MT 42 2M XI

Type	Style	Form
MT Micro Button	42	n/a
MA Micro Display		

Suffix/Connection						
Suffix	Switch	Voltage	Current	Terminal blocks		
				AWG	Torque	Wire type
IX NA	SPST-NO	6 - 30 V DC	2 A	28 - 14	2.25 Lb. In.	Cu
		48 V DC	0.7 A			
		48 V AC	0.7 A			
IX bicolor	SPST-NO	0.02 - 30 V AC	0.05 A	28 - 18	1,5 Lb. In.	Cu
		0.02 - 30 V DC				
2M XI	SPST-NO	30 V DC	0.5 A	28 - 18	1,5 Lb. In.	Cu
		SPDT	30 V DC 50 V AC			



Housing		Touchplate/Plate		Protection		LED Color		LED Voltage/LED Current		
10	#8 Stainless steel, mirrored	01	Stainless steel, non-directional	00	Protection IP 40 (IEC 60529) Type 1 (UL50) Class 0	unicolor		IX NA		
	11		02			#8 Stainless steel, TiN (brass color), mirrored	10	red	6 V DC ⁽²⁾	40 mA
							20	blue	12 - 42,4 V DC ⁽²⁾	40 mA
							30	green	30 - 42,4 V AC ⁽²⁾	40 mA
12	03	#8 Stainless steel, black color, mirrored	40	white	IX bicolor					
			50	yellow	12 - 30 V DC ⁽²⁾	45 mA				
13	#8 Stainless steel, bronze color, mirrored	04	#8 Stainless steel, mirrored	bicolor		30 - 42,4 V DC ⁽²⁾	45 mA			
				13	red/green	2M XI				
				31	green/red	6 V AC/DC ⁽²⁾	40 mA			
				23	blue/green	12 V AC/DC ⁽²⁾	40 mA			
				25	blue/yellow	30 V AC/DC ⁽²⁾	40 mA			
				42	white/blue					
				21	Plastic, red ⁽¹⁾					

(1) only MA42
(2) Class2 (UL508) and limited Voltage/Current circuit