

Product Code | Code Produit | Código Producto

STYLE
42

RT 42 IX NA | RA 42 IX NA | RT 42 IX bicolor NA | RT 42 2M XI NA

Type		Style	Form
RT	Round Button	42	n/a
RA	Round Display		

Suffix/Connection						
Suffix	Switch	Voltage	Current	Terminal blocks		
				AWG	Torque	Wire type
IX NA	SPST-NO	6 - 30 V DC	2 A	28 - 14	2.2 Lb. In.	Cu
		120 V DC	0.05 A			
		120 V AC	0.7 A			
IX bicolor NA	SPST-NO	0.02 - 30V AC 0.02 - 30V DC	0.05 A	28 - 18	1.5 Lb. In.	Cu
2M XI NA	SPST-NO	30 V DC	0.5 A	28 - 18	1.5 Lb. In.	Cu
		30 V DC 50 V AC	0.5 A 1 A			

RT 42 IX NA
21 - 05 - 00 - 10 12 - 120 V

Housing	Touchplate/Plate	Protection	LED Color	LED Voltage/LED Current
20 #8 Stainless steel, mirrored 36-V2A-p 21 #8 Stainless steel, TiN (brass color), mirrored 36-V2A, TiN-p 22 #8 Stainless steel, black color, mirrored 36-V2A, black-p 23 #8 Stainless steel, bronze color, mirrored 36-V2A, bronze-p	01 Stainless steel, non-directional V2A, matt 02 Stainless steel, TiN (brass color), non-directional V2A, TiN, matt 03 #8 Stainless steel, black color, mirrored V2A, black 04 #8 Stainless steel, mirrored V2A, poliert 05 #8 Stainless steel, TiN (brass color), mirrored V2A, TiN, poliert 20 Plastic, clear ⁽¹⁾ 21 Plastic, red ⁽¹⁾ 40 #4 Stainless steel V2A, gebürstet, 0.5 mm	00 Protection IP 40 (IEC 60529) Type 1 (UL50) Class 0	unicolor 10 red 20 blue 30 green 40 white 50 yellow bicolor 13 red/green 31 green/red 23 blue/green 25 blue/yellow 42 white/blue	IX NA 6 V DC 40 mA 12 - 120 V DC 0.4 W - 0.8 W 30 - 120 V AC IX bicolor 12 - 30 V DC 45 mA 30 - 48 V DC 45 mA 2M XI 6 V AC/DC 40 mA 12 V AC/DC 40 mA 30 V AC/DC 40 mA

(1) only RA42



E469509
Elevator Accessory

Surrounding air temperature:
max. +55°C/ +131°F



SCHAEFER