

Product Code | Code Produit | Código Producto

VB 42 NA | VD 42 NA

STYLE
42

Type		Style	Form		Suffix/Connection						
Type	Description	Style	Form	Detail	Suffix	Switch	Voltage	Current	Terminal blocks		
									AWG	Torque	Wire type
VB	Vandalism-proof Button	42	M	Illuminated dot (center)	NA	SPST-NO	30 V DC	0.1 A	28 - 18	1.5 Lb. In.	Cu
VD	Vandalism-proof Display		n/a			SPDT	48 V DC 50 V AC	0.1 A 0.1 A			

VB	42	M	NA	
04	01	02	20	12 - 30 V

Housing		Touchplate/Plate		Protection		LED Color		LED Voltage/LED Current	
04	Cr-p (Chrome, polished)	01	Stainless steel, non-directional V2A, <i>mat</i>	02	Protection against water and vandalism IP 55 (IEC 60529) Type 3R (UL50) <i>Class 2</i>	10	red	6 V DC	20 mA
05	Cr-m (Chrome, matted)	03	#8 Stainless steel, black color, mirrored V2A, <i>black</i>			20	blue	12 - 30 V AC/DC	20 mA
		09	Aluminum, untreated ⁽¹⁾ <i>AlMg3 EV1, silberfarben</i>	03	Protection against water and vandalism IP 54 (IEC 60529) Type 3R (UL50) <i>Class 3+</i>	30	green		
						40	white		
						50	yellow		

(1) only VB 42 M NA



Surrounding air temperature:
max. +55°C / +131°F

E469509
Elevator Accessory

